



MAKES IT BRIGHT

UV METER | DIGITAL | EASY TO OPERATE

- An instrument for accurate measurement of UV-A radiation
- Measuring range: 0.1 – 200.000 $\mu\text{W}/\text{cm}^2$
- Spectral sensitivity: 315-390 nm
- Accuracy: better than $\pm 4\%$ (± 1 in last digit)
- Power supply: 9 volt battery, type PP3 Alkaline (approx. 350 hrs operation)
- Dimensions: 135x75x35 mm or 5.3" x 2.9" x 1.4"
- Weight: 0.19 kg or 6.7oz.
- Easy to operate with both automatic zeroing and on/off switch
- Includes a four-position range selection and a hold button for retaining the display value
- Available models: **single point or 5-point calibration**



VISIBLE LIGHT METER | LUX & FOOT CANDLE | NON FLUORESCENT SENSOR

- An instrument for accurate measurement of illumination
- Provides measurements in both metric lux (lx) and imperial foot candle (fc)
- The sensitivity ranges are 0.1 – 200.000 lx and 0.01 – 20.000 fc.
- Easy to operate with both automatic zeroing and on/off switch
- Includes a four-position range selection and a hold button for retaining the display value
- Traditional visible light meters are adapted to the lower intensity Mercury Vapour Technology and its specific spectral UV-A
- The Labino Visible Light Meter is the first instrument specifically designed without a fluorescent sensor for high intensity UV-lamps
- Detector: Non-fluorescent silicone photodiode
- Accuracy meter: better than $\pm 3\%$ (± 1 in last digit)
- Power supply: 9 volt battery, type PP3 alkaline (approx. 350 hrs operation)
- Dimensions: 135x75x35 mm or 5,3" x 2,9" x 1,4"
- Weight: 0.19 kg or 6.7 oz.



UV & VISIBLE LIGHT | CABLE CONNECTED DETECTOR

- Labino offers two cable connected detector models: the Visible Light Meter with Cable Connected Detector and the UV-Meter with Cable Connected Detector. Both instruments provide an accurate measure of illumination. Available models: **single point or 5 point calibration**
- The technical specifications of these meters are the same as for our regular Visible Light Meter and UV-Meter, with one exception - the light detector is connected to a cable which enables the user the possibility of standing far away from the point at which the light reading will be taken. The standard cable length is 5 meters and it's possible to order a longer cable at an additional per meter charge.



METER CASE | PROTECT | TRANSPORT

Our meter case both protects your meters and makes transporting them easier. The case is available with an interior design made for one or two meters – with or without the cable connected detectors.